

(19) World Intellectual Property Organization
International Bureau



PCT



(43) International Publication Date
20 March 2008 (20.03.2008)

(10) International Publication Number
WO 2008/033409 A1

(51) International Patent Classification:

A61B 17/068 (2006.01) A61B 17/072 (2006.01)

(21) International Application Number:

PCT/US2007/019833

(22) International Filing Date:

12 September 2007 (12.09.2007)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/825,534 13 September 2006 (13.09.2006) US

11/542,457 3 October 2006 (03.10.2006) US

(71) Applicant (for all designated States except US):

BAROSENSE, INC. [US/US]; 3908 Patriot Drive,
Suite 170, Durham, NC 27703 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CREWS, Sam

[US/US]; 1325 Bryant Street, Palo Alto, CA 94301 (US).

SWODE, Brett [US/US]; 24812 Woodfield School Road,

Gaithersburg, MD 20882 (US). COLE, Dave [US/US];
1548 Lago Street, San Mateo, CA 94403 (US). SMITH,
Andrew [US/US]; 2240 Pacific Avenue, #304, San Fran-
cisco, CA 94115 (US).


(74) Agents: FROST, Kathleen, A. et al.; Stallman & Pollock
LLP, 353 Sacramento Street, Suite 2200, San Francisco,
CA 94111 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG,
ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK,
LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW,
MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL,
PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: ENDOSCOPIC PLICATION DEVICE AND METHOD



(57) Abstract: In a method of stapling layers of tissue within a body cavity, an engaging instrument is passed between a stapler cartridge and anvil and used to engage a region of tissue. The engaging instrument is retracted to move the engaged tissue into the stapling position, and driving staples from the cartridge through at least two layers of the engaged tissue. The method and associated system may be used to form plications in body tissue, such as stomach wall tissue. Staples simultaneously driven through tissue may simultaneously capture a reinforcing elements positioned adjacent the cartridge and/or anvil prior to stapling.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

ENDOSCOPIC PLICATION DEVICE AND METHOD

5 FIELD OF THE INVENTION

The present invention relates generally to the field of systems and methods for performing endoscopic surgery, and specifically to systems and methods for endoscopic plication of tissue within body cavities.

10 BACKGROUND OF THE INVENTION

An anatomical view of a human stomach S and associated features is shown in Fig. 1A. The esophagus E delivers food from the mouth to the proximal portion of the stomach S. The z-line or gastro-esophageal junction Z is the irregularly-shaped border between the thin tissue of the esophagus and the thicker tissue of the stomach wall. The
15 gastro-esophageal junction region G is the region encompassing the distal portion of the esophagus E, the z-line, and the proximal portion of the stomach S.

Stomach S includes a fundus F at its proximal end and an antrum A at its distal end. Antrum A feeds into the pylorus P which attaches to the duodenum D, the proximal region of the small intestine. Within the pylorus P is a sphincter that prevents backflow
20 of food from the duodenum D into the stomach. The middle region of the small intestine, positioned distally of the duodenum D, is the jejunum J.

Fig. 1B illustrates the tissue layers forming the stomach wall. The outermost layer is the serosal layer or "serosa" S and the innermost layer, lining the stomach interior, is the mucosal layer or "mucosa" MUC. The submucosa SM and the multi-layer muscularis
25 M lie between the mucosa and the serosa.

Prior applications, including Attorney Docket No. BARO-720PCT, WO 2005/037152 (incorporated herein by reference in its entirety) describe methods according to which medical implants are coupled to tissue structures formed within the stomach. According to these applications, devices for inducing weight loss (e.g. by
30 restricting and/or obstructing flow of food into the stomach, and/or by occupying a portion of the stomach volume) may be coupled to tissue tunnels or plications P (Fig. 2) formed from stomach tissue.

For example, US Application No. 11/439,461, Filed May 23, 2006, Attorney Docket BARO 910 (incorporated herein by reference in its entirety), describes a
35 Restrictive and/Or Obstructive Implant System for Inducing Weight Loss. In one

embodiment, flexible loops 2 (Fig. 3) are coupled to tissue plications P (Fig. 2) formed in the gastroesophageal junction region of the stomach. An implant, such as a flow restrictive and/or obstructive implant 4 (Fig. 4), is passed through the loops 2 and thus retained in the stomach as shown in Fig. 5.

5 U.S. Application No. 11/542,457, filed October 3, 2006 (Attorney Docket No. BARO-1110) discloses other implants, including a restrictive pouch having anchors extending from its outer surface. During implantation, the anchors are inserted to cutouts/holes formed in plicated tissue.

10 In other instances, tissue plications may themselves be sufficient to provide the necessary treatment. For example, the plications may be used to reduce stomach volume or form a flow restriction within the stomach. Two or more plications may be drawn together and retained in some way, such as to form a restriction and/or reduce stomach volume, as also described in U.S. Application No. 11/542,457, filed October 3, 2006.

15 Other types of implants may be coupled to such plications or other tissue structures for a variety of purposes. These implants include, but are not limited to gastric space occupiers, prosthetic valves for the treatment of gastro-esophageal reflux disease, gastric stimulators, pH monitors and drug eluting devices that release drugs, biologics or cells into the stomach or elsewhere in the GI tract. Such drug eluting devices might include those which release leptin (a hormone which creates feelings of satiety), Ghrelin
20 (a hormone which creates feelings of hunger), octreotide (which reduces Ghrelin levels and thus reduces hunger), Insulin, chemotherapeutic agents, natural biologics (e.g. growth factor, cytokines) which aid in post surgery trauma, ulcers, lacerations etc. Still other implants might be of a type which might provide a platform to which specific cell types can adhere, grow and provide biologically-active gene products to the GI tract, and/or a
25 platform for radiation sources that can provide a local source of radiation for therapeutic purposes, or provide a platform whereby diagnostic ligands are immobilized and used to sample the GI tract for evidence of specific normal or pathological conditions, or provide an anchor point for imaging the GI tract via cameras and other image collecting devices.

Prior applications listed above address the desirability of forming tissue plications,
30 pockets or tunnels in a way that regions of serosal tissue (i.e. the tissue on the exterior surface of the stomach) are retained in contact with one another. Over time, adhesions formed between the opposed serosal layers create strong bonds that can maintain the plication over extended durations, despite the forces imparted on them by abdominal movement and implanted devices. More durable plications can be created by placing any
35 of a number of materials and/or substances (e.g. injectable sclerosing agents) between the

serosal surfaces prior to plicating the serosal surfaces together. One example of material suitable for this purpose is polypropylene mesh, commonly used for hernia repair, which when inserted in the plication fold provides a durable anchoring position within the GI tract.

5 Regardless of the application for which a plication is being formed, it is highly desirable to form that plication using steps carried out from within the stomach using instruments passed down the esophagus, rather than using more invasive surgical or laparoscopic methods.

 The present application describes endoscopic plicators which may be passed
10 transorally into the stomach and used to plicate stomach tissue by engaging tissue from inside of the stomach and drawing it inwardly. A section of stomach wall tissue drawn inwardly will be referred herein as a "pinch" of tissue, although it may be drawn inwardly using suction or other means. In preferred embodiments, a retracting component draws tissue into the path of travel of a stapler head. Vacuum and/or mechanical retractors may
15 be used for retraction. By drawing a portion of the stomach wall between the stapler head and anvil, the retracting component causes sections of serosal tissue on the exterior of the stomach to be positioned facing one another. The disclosed plicators deliver staples to secure the opposed sections of tissue to one another, but instead may deliver sutures or other means for maintaining contact between the tissue sections at least until serosal
20 bonds form between them. The plicator may pass a mesh element and/or sclerosing agent through the stomach wall into position between the opposed regions of serosal tissue thus enhancing serosal bonding. Each of these steps may be performed wholly from the inside of the stomach and thus can eliminate the need for any surgical or laparoscopic intervention. Medical devices may then be attached to the anchor for retention within the
25 stomach.

 While this application describes plication systems and methods with respect to the formation of plications in stomach tissue, the embodiments described herein have equal applicability for forming plications in parts of the body within or outside the GI system.

30 BRIEF DESCRIPTION OF THE DRAWINGS

 Fig. 1A is a schematic illustration of a human stomach and a portion of the small intestine.

 Fig. 1B is a cross-sectional perspective view of a portion of a stomach wall, illustrating the layers of tissue forming the wall.

35 Fig. 2 is a perspective view of a plication system.

Fig. 3 is a perspective view of the system of Fig. 2 with the vacuum head in a tissue engaging position.

Fig. 4 is a perspective view of the system of Fig. 3, showing tissue being engaged by the vacuum head and compressed by the system.

5 Fig. 5 is a cross-section view similar to the view of Fig. 4.

Fig. 6 is similar to Fig. 5 and shows activation of the staple driver to fire staples from the cartridge.

Figs. 7A through 7E are a sequence of drawings illustrating use of an engaging element to retract tissue that has been engaged by the vacuum head.

10 Fig. 8 is a perspective view of a second embodiment of a plication system.

Fig. 9 is an exploded view of the retracting component of the embodiment of Fig. 8.

Fig. 10A is a perspective view of an embodiment of an expandable vacuum chamber, shown in the compressed position.

15 Fig. 10B is a perspective view of the vacuum chamber of Fig. 10A in the expanded position.

Figs. 11A and 11B are plan views illustrating staple patterns.

Figs. 12A – 12C are plan views illustrating interlocking staple patterns.

Figs. 13A and 13B are plan views of reinforcing rings.

20 Fig. 14A is a perspective view showing the reinforcing ring of Fig. 13B on a stapler anvil.

Fig. 14B is a plan view of the reinforcing ring and anvil of Fig. 14A.

Fig. 14C is a perspective view showing the reinforcing ring of Fig. 13A on a staple cartridge.

25 Figs. 15A and 15B are plan views of a tissue plication, in which Fig. 15A shows the side of the plication positioned on the staple cartridge side of the plicator, and Fig. 15B shows the side of the plication position on the anvil side of the plicator.

Figs. 16a and 16b are plan views showing staple reinforcements suitable for use with linear staple patterns.

30 Fig. 17 schematically illustrates the use of the staple reinforcements of Fig. 16b to support fasteners for engaging tissue plications to one another.

Fig. 18A illustrates an alternative engaging element, and Figs. 18B through 18E illustrate the sequence of steps for deploying the engaging element of Fig. 18A and retaining the engaging element within a tissue plication.

35 Fig. 19 illustrates an alternative engaging element and deployment hoop.

Figs. 20A and 20B illustrate yet another engaging element being deployed from the hollow needle of the vacuum head.

Figs. 21A, 21B and 21C illustrate alternative reinforcing elements. In Fig. 21C, the reinforcing element is shown being deployed from a hollow tube.

5 Fig. 22A is a perspective view of an expandable frame for deploying a reinforcing element. Fig. 22B shows a reinforcing element on the frame of Fig. 22A.

Figs. 23A and 23B are cross-section views illustrating hydraulic systems that may be used for tissue compression and staple driving in the system of Fig. 2.

10 DETAILED DESCRIPTION OF THE DRAWINGS

Plication System

Fig. 2 illustrates one embodiment of a system 10 for tissue plication that is suitable for endoscopic use, as well as surgical or laparoscopic use if desired.

Generally speaking, system 10 includes a main shaft 11 having a distal portion
15 extendable through the esophagus into the stomach. The distal portion of the main shaft 11 includes a retracting component 12 and a stapling component 13 comprised of an anvil 40 and a staple head 42. During use of the system 10, the retracting component 12 is used to engage stomach wall tissue and draw the tissue into a position between the anvil 40 and
20 plication. By drawing a "pinch" of the stomach wall inwardly and then stapling the tissue, regions of serosal tissue are stapled to one another. Over time, these serosal tissue layers will adhere to form relatively strong bonds giving the plications sufficient durability to support implants within the stomach.

Retracting component 12 is provided with a vacuum head 14 and a flexible tube
25 16. Tube 16 preferably includes an insertion configuration in which it extends approximately longitudinally relative to the main shaft 11 for streamlined advancement of the tube 16 through the esophagus. Tube 16 is equipped with pull-wires (not shown) and/or alternative means for articulating or retroflexing the vacuum head 14 as needed for proper positioning within the stomach.

30 Vacuum head 14 defines a vacuum chamber 18 having an opening that, during use, is positioned into contact with stomach tissue so as to draw the tissue into the chamber 18. Vacuum chamber is preferably formed of a flexible material such as silicone, urethane or other suitable materials. Tube 16 is fluidly coupled to a source of negative pressure such as a syringe or vacuum pump such that application of suction to
35 the tube 16 creates a vacuum in the vacuum chamber.

A hollow needle 20 is advanceable through the tube 16 into the vacuum chamber 18. Hollow needle 20 includes a pointed distal tip sufficiently sharp to penetrate stomach wall tissue (Figs. 7A – 7B) when advanced against tissue drawn into the vacuum chamber. An optional tissue engaging element (not shown in Figs. 2-6) is positioned
5 within the hollow needle 20. As shown in Figs. 7C – 7E, the tissue engaging element is deployable from the hollow needle 20 and placed in an expanded state after the needle 20 has been advanced through tissue, and it is then withdrawn proximally using an attached tether or catheter following deployment to maintain engagement with the tissue.

Various types of engaging elements may be used for this purpose. In the
10 embodiment shown in Fig. 7D, the engaging element 22a may be a balloon 24 mounted on a small diameter catheter 26 extendable through the needle 20. After the balloon 24 is expanded on the serosal side of the stomach wall, tension is applied to the catheter 26 as shown in Fig. 7E to hold the retracted tissue between the anvil 40 and staple head 42 (not shown in Figs. 7A - 7E but discussed below) for stapling. The vacuum chamber 18 may
15 be withdrawn from the tissue to move it out of the area between the staple cartridge and anvil. Staples are then driven through the tissue in the direction of arrow A. The balloon may be removed after stapling or it may be left in place within the body. If the balloon is to be left in the body, it may be formed of a biodegradable or bioerodible material, or a more permanent biocompatible material.

20 As mentioned previously, stapling component 13 includes an anvil 40 and a stapler head 42. Although Figs. 2 – 6 show the head 42 positioned distally of the anvil 40, in other embodiments the positions of these features might be reversed. Likewise, while in the illustrated embodiments the staple head is advanced to compress the tissue, in other embodiments the anvil might instead be advanced.

25 The stapling component 13 is pivotable relative to the main shaft 11 so that once the stapling component 13 is positioned within the stomach, it may be moved laterally towards the stomach wall. In the Fig. 2 embodiment, anvil 40 is mounted to an articulated base 52 coupled to the main shaft 11 at pivot point 54 (Fig. 5), allowing for rotation of the base (and thus the stapling component 13) relative to the main shaft 11. The base 52 is
30 moveable to a longitudinal position (not shown) relative to the shaft to facilitate streamlined movement of the system 10 through the esophagus. As shown in Fig. 5, a motor driven worm screw 56 is activated to articulate the base 52.

As best shown in Fig. 5, staple head 42 includes a staple cartridge 44 containing staples (not visible in the drawing), and a staple driver 46 positioned to drive staples from
35 the cartridge 44 when it is advanced proximally into contact with the staples. Fluid lines

58a, 58b extend from the cartridge 44 and staple driver 46 respectively and are coupled to air, gas or other fluid (any of which will be referred to as "fluid") sources positioned external to the body. During use, fluid or gas pressure is directed through fluid line 58a and used to advance the staple cartridge 44 into contact with tissue positioned between the anvil 40 and cartridge 44 as shown in Fig. 4, thereby compressing the tissue. In an alternative embodiment, the fluid line 58a may be replaced with a cable configured to drive a lead screw that, when activated, advances the staple cartridge 44 to compress tissue disposed within the gap between the anvil 40 and the staple cartridge 44.

Once tissue is compressed between the cartridge 44 and anvil 40, fluid/gas is then directed through fluid line 58b to pressurize cylinder 48 sufficiently to drive the staple driver 46 into contact with staples positioned in the staple cartridge 44. A tissue cutting element 50, which in the illustrated embodiment is a tubular element having a sharpened end, is coupled to the staple driver 46 such that it will core through the tissue during stapling to form a hole in the plication.

Figs. 23A and 23B show collapsible hydraulic systems that may be used to advance the cartridge 44 and staple driver 46.

System 110 of Fig. 23A allows for sequential movement of the cartridge and the driver allowing for compression and then stapling. System 110 includes nested cylinders 112a, 112b and 112c, fluid inlets 114a, 114b and 114c, and o-ring seals 116a-d. When fluid pressure is introduced into the system via inlet 114a, cylinder 112b advances to the left. Once seal 116b of cylinder 112b crosses over inlet 114b, fluid pressure is applied to cylinder 112a through inlet 114c, causing cylinder 112a to begin moving towards the left of the drawing. This arrangement can be used to first compress (e.g. using staple cartridge coupled to cylinder 112b), and to then staple (e.g. using a staple driver coupled to cylinder 112a) the tissue using a single source of fluid or gas pressure.

System 111 of Fig. 23B is a telescoping fluid power actuator that may be used when the length of the path of travel needed for a feature (e.g. the stapler driver, cartridge, and/or anvil) would require a cylinder that is longer than can be accommodated by the environment (e.g. the stomach). System 111 includes cylinders 118a, 118b and 118c, inlets 120a and 120b, and seals 122. Pressure applied at inlet 120a will cause cylinder 118a (which may be coupled to the cartridge) to advance to the left. Once cylinder 118a has moved a distance "l", it will engage with a shoulder 124 on cylinder 118b, causing cylinder 118b to travel with cylinder 118a as cylinder 118a continues to move. In this arrangement, a long stroke for cylinder 118a is gained from a short fluid power system.

Fig. 8 shows an alternative embodiment of a modified plication system 10a which utilizes rigidizable cables 80 to deflect the stapling component 13 relative to the main shaft 11. Cables 80 are preferably formed of a plurality of spine elements 82 strung onto a pull wire (not shown). Fluid lines 58a, 58b may extend through holes in the spine elements, or they may be separate from the cables 80. When tension is applied to the cables using actuators positioned outside the body, the spine elements 82 engage one other to stiffen the cable. The spine elements 82 may be shaped such that the cable will assume a predetermined bend when tension is applied to them.

In the Fig. 8 embodiment, a rigidizable cable 86 also carries the vacuum chamber 18a. Cable 86 includes a pull wire (not shown) extending through spine elements 88. The spine elements 88 are shaped to orient the chamber 18a for advancement between the anvil 40 and cartridge 44. Cable 86 may extend from a sheath 89 that is longitudinally extendable from a lumen in the main shaft 11.

Vacuum chamber 18a may be foldable or compressible for positioning within the sheath 89. Fig. 10A shows a folded vacuum chamber 18b beginning to expand as it exits the distal end of sheath 89, and Fig. 10B shows the vacuum chamber 18b fully expanded after exiting the sheath 89. Fig. 10A illustrates that in alternative embodiments, endoscopes 98 and/or other instruments may be passed through the vacuum chamber 18b to give access and/or visualization to the stomach wall or other organs or tissues. In the Fig. 8 embodiment, a collar 96 is positioned on the main shaft 11 for receiving endoscope 98.

Fig. 9 is an exploded view of the vacuum chamber 18a of the Fig. 8 embodiment, and illustrates that a pair of gripping jaws 90 is positioned within the vacuum chamber 18a. The jaws 90 are constructed using a linkage arrangement and are controlled using a pull wire extending through a back plate 92 of the vacuum chamber 18a, through spine elements 88 (Fig. 8), and to the proximal end of the plicating system outside the body. Before vacuum is applied, the jaws are moved to an open position. When vacuum pressure draws tissue into the vacuum chamber 18a, the jaws 90 are closed to engage the tissue.

The Fig. 8/9 vacuum chamber 18a additionally includes stabilizing arms 94 extending into the vacuum chamber 18a. The stabilizing arms are retained in contact with the interior walls of the chamber 18a to prevent the chamber from collapsing when vacuum is applied. The arms may be moveable between closed and opened positions to allow the vacuum chamber to collapse for passage through the esophagus, or they may remain fixed in the opened position.

Plication Reinforcements

Reinforcements of various types may be implanted in or on plications formed using the plication system. Such reinforcements may function to reinforce the staple array, help to more evenly distribute the forces applied to the tissue by the staples, and/or
5 facilitate bonding between the opposed serosal layers. Suitable reinforcements include ones positionable on or between the serosal tissue layers ("serosal side reinforcements"), as well as those delivered on the side of the mucosal tissue ("mucosal side reinforcements").

For serosal side reinforcements, a reinforcement similar to engaging element 22a
10 described in connection with Fig. 7D may serve as a permanent or semi-permanent implant that will reinforce the staple array applied to the tissue and/or facilitate serosal tissue bonding between the layers of stomach wall tissue that are to be stapled together. For this purpose, the material may be a synthetic or non-synthetic mesh (formed of nitinol, polyester, or other natural or synthetic material), porous or non-porous material,
15 slotted material, or any other material through which adhesions will form or onto which tissue will grow. Examples include, but are not limited to, polypropylene, materials sold under the trade names Goretex or Dacron, or tissue graft material such as the Surgisis material sold by Wilson Cook Medical, Inc. The material may be treated with tissue-ingrowth promoting substances such as biologics. In an embodiment shown in Fig. 18A,
20 the reinforcement 22b is a mesh/braid embedded in or coated with a dissolvable or bioabsorbable coating. The reinforcement 22b is preferably positioned in a manner similar to that described in connection with the balloon of Fig. 7D. Specifically, vacuum chamber 18 is used to engage a region of tissue where a plication is to be formed. Hollow needle 20 is advanced from within the chamber 18 through the stomach wall, and the
25 reinforcement 22b is advanced from the hollow needle and inflated to a toroidal shape between the opposed regions 104 of serosal tissue. The reinforcement 22b may optionally be used for retraction of the stomach wall via application of tension on the tether 33 as shown in Fig. 18D. Staples driven through the tissue pierce and deflate the inflated reinforcement as shown in Figs. 18D and 18E, and capture the deflated
30 reinforcement between the opposed serosal tissue layers. The reinforcement is left in place between the two layers of stomach wall tissue after stapling. The coating on the deflated balloon dissolves, exposing the interstices of the underlying mesh or porous material to serosal growth.

As shown in Fig. 19, the reinforcement 22c may instead be a mesh disk 30
35 detachably carried (e.g. using sutures 32) on a wire hoop 34 extendable through needle 20

in a compressed shape and then self-expandable to the illustrated position to expand the mesh on the outside of the stomach. The sutures 32 are severed during stapling, leaving the mesh in place between the plicated tissue layers. The hoop 34 is withdrawn into the needle 20 and removed from the body.

5 In another embodiment shown in Figs. 20A and 20B, the reinforcement 22d may be an elongate nitinol mesh or braid backbone 35 that may be positioned longitudinally within the hollow needle 20, but that is shape set to assume a circular or other suitable configuration once released from the hollow needed between the serosal tissue layers. In modifications to this concept shown in Figs. 21A – 21C, the reinforcement 22e may be a
10 wire 37 or ribbon shape set to assume one of a variety of expanded configurations when it is pushed out of the hollow needle 20. In the expanded configuration, the wire may assume a pattern shaped such that when it is positioned between serosal tissue layers, it will be captured by staples advanced through the tissue. As with the other reinforcements disclosed above, the pattern may be annular as in Figs. 21A or 21C, or it may be disk-like
15 as in Fig. 21B. Moreover, while the patterns are shown to have an approximately circular silhouette, other shapes may instead be used.

 In another embodiment shown in Figs. 22A and 22C, a reinforcement 22f (which may be formed of a polyester fabric or other material including those listed elsewhere in this application) is carried by a frame 106 having a plurality of outwardly extending arms
20 108 that spring to an expanded position when released from hollow tube 20. The reinforcement 22e is deployed using hollow needle 20 in a manner similar to those described above. Specifically, the hollow needle 20 is pierced through engaged stomach wall tissue, and the frame is advanced out the distal end of the needle 20 to allow arms
25 108 to spread to the expanded position shown in Figs. 22A and 22C, thereby expanding the reinforcement 22e between the opposed serosal layers. The element is fixed between the layers by the staples driven through the opposed regions of stomach wall, and the frame is withdrawn from the needle and out of the body.

 Mucosal side reinforcements may take the form of reinforcements that are positioned on or adjacent to one or both of the mucosal surfaces lining the “pinch” of
30 tissue that will form the plication. These reinforcements may be features of the staples or staple arrays, or they may be separate components engaged by staples as the staples are advanced through the tissue.

 Referring to Fig. 21A, conventional stapling procedures will often include two parallel rows of staples, in which the staples in one row are laterally offset from the
35 staples of the other row. According to the disclosed method, it is useful to employ this

technique to the circular staple pattern delivered using the plicator 10, to produce two concentric rings of offset staples, as shown in Fig. 11B. It has been found to be additionally beneficial to form mucosal side reinforcements by linking or interlocking the staples to provide greater structural reinforcement to the stapled tissue and/or to more evenly distribute forces applied to the tissue by the staples. Linked staple arrays may be formed by arranging the staples 70 in the cartridge of the plicator 10 in a single circular pattern to interlock as shown in Fig. 12A, or in a double circular pattern with two concentric rings of interlocked staples. The staples 70a may be curvilinear so as to form a locking pattern shown in perspective view of Fig. 12B. A linear arrangement of staples 70 may also be linked as shown in Fig. 12C.

In alternative embodiments, staples are linked together by reinforcing members formed of metallic or polymeric materials, such as nitinol, titanium, stainless steel PEEK, or other biocompatible materials. According to these embodiments, the reinforcing members are positioned on one or both of the mucosal sides of the "pinch" of tissue engaged by the plication system such that they are captured by staples being driven through the tissue. In a preferred embodiment, the staples capture a cartridge side reinforcing ring 72 (Fig. 13A) as they leave the cartridge and/or capture an anvil side reinforcing ring 74 (Fig. 13B) as the anvil shapes and bends them. Upon completion of the plication, the staples are linked to one another so that they cannot separate or expand radially. The use of the reinforcing rings is advantageous compared with prior art staple buttressing materials such as sheets formed of bovine pericardium or hydrogel, both of which are penetrated (and thus potentially compromised) by staples as they are driven through the tissue. The open structure or lattice pattern of the reinforcing rings provides openings for the staples to pass through as well as supportive members for the staples to wrap around – so that the staples capture but do not penetrate the ring material. Over time, tissue may grow into the lattice structure and/or around the supportive members. The proportions of the ring, such as the sizes of the openings in the lattice structure, may be adjusted to increase or decrease the amount of ingrowth that might occur.

The reinforcing rings are preferably provided separate from the staples although they instead may be integral with the staples. In this embodiment, ring 74 is positioned against the staple anvil 40 as shown in Figs. 14A and 14B. The anvil may include retaining elements to maintaining the ring's position on the anvil. Ring 72 is seated within the cartridge 44, with the staples 70 aligned with their prongs 76 extending through openings 73 in the ring 72. Alternatively, the cartridge may have retaining elements to hold the ring in place prior to stapling.

When staples 70 are driven from the cartridge, they advance further through openings 73, capturing ring 72 against the adjacent mucosal tissue as shown in Fig. 15A. The staple legs/prongs 76 pass through the stomach wall tissue into contact with the indentations 78 of the anvil 40. When they contact the anvil 40, the prongs 76 fold
5 around the staple ring 74 to capture the ring and interlock the staples on the anvil side of the plication as shown in Fig. 15B. Rings or other interlocking elements of this type may be used with single- or double- staple row configurations.

Rings 72, 74 are shown as generally circular, although alternative reinforcements of different shapes and patterns may also be used, including those shaped to
10 accommodate linear, oval and other staple patterns.

Figs. 16a and 16b show two examples of reinforcements 75a, 75b useful for linear staple patterns. As shown, reinforcements are similar to the ring 72 in their use of a plurality of interconnecting members that define openings 73a for receiving staple legs. The legs of any given staple may pass through two laterally positioned openings 73a,
15 longitudinally positioned openings 73a, just a single opening, or any other combination. These reinforcements may be used with linear staplers in a manner described above with respect to the circular staplers. The reinforcements may include members 77 positioned to receive implants that might be used within the body (e.g. pH monitors or other sensors, stimulation/pacing leads, etc.). Fig. 17 illustrates use of the loops 77 to support fasteners
20 79a, 79b in a system for engaging one tissue plication to another tissue plication. Staples 70 driven through the openings 73a engage the reinforcements and form the plications. The fasteners 79a, 79b are then brought into engagement with one another to draw and couple the plications together. This may be used to form a restriction and/or reduce stomach volume, or for other purposes.

25 The disclosed reinforcements may be sold as individual components that may be used together with commercially available staplers to reinforce the lines/rings of staples to be delivered by those staplers.

Exemplary Method of Use

One method of using the illustrated system will next be described with reference
30 primarily to Figs. 8 and 9.

In preparation for use, the orientation of the staple head 42 and the vacuum chamber 18a are adjusted using the appropriate pullwires to place them in their longitudinal positions.

Next, the assembled plicator 10a is passed into the stomach S via the esophagus,
35 preferably through a protective sheath passed through the esophagus. Endoscope 98 is

also passed into the stomach to provide visualization of the procedure. The endoscope is preferably mounted to plicator 10a, or it may be a separate component.

The plicator 10a is advanced towards a target location at which a plication is to be formed. The rigidizable cable 86 is manipulated using pull wires to extend vacuum
5 chamber 18a between the fluid lines 58a, 58b and against adjacent stomach tissue. Suction is applied to the vacuum chamber 18 to draw stomach tissue into the vacuum chamber. The gripper arms 90 are closed to pinch the tissue within the chamber, and the vacuum chamber 18a is withdrawn from between the fluid lines 58a, 58b, carrying the engaged tissue with it (see Fig. 4). Consequently, a pocket 100 forms in the tissue such
10 that if the stomach were to be viewed from the outside a depression in the stomach wall would be visible. Serosal tissue surfaces 104 line the outside surfaces of the pocket 100. If gripper arms are not used, suction maintained to stabilize the tissue within the vacuum chamber.

If additional stabilization of the tissue is desired, such as during use of the Fig. 2
15 embodiment, hollow needle 20 may be advanced through the engaged tissue as shown in Figs. 7A and 7B, and balloon 24 is inflated within the pocket 100 as shown in Figs. 7C and 7D. As shown in Fig. 7E, the inflated balloon 24 is withdrawn using catheter 26, thus retracting the tissue surrounding the pocket 100. Alternatively, the engaging element 22b of Fig. 8A, or element 22d of Figs. 10A and 10B may be deployed and used in similar
20 fashion. If element 22c of Fig. 9 is to be used, the hoop 34 is advanced through the hollow needle 20 into the pocket 100 where it springs to its opened configuration to expand the mesh element 22c.

Referring again to Fig. 8, once the tissue has been drawn between the fluid lines 58a, 58b, fluid is driven through fluid line 58a to bring the staple cartridge 44 into contact
25 with the tissue and to compress the tissue between the cartridge 44 and the anvil 40 (see Fig. 4). Once the tissue is fully compressed, fluid pressure is via line 58b, causing the staple driver 46 to advance into contact with staples in the cartridge 44, thus driving the staples through the tissue and simultaneously forming a hole or incision through the layers of stomach wall tissue. The sharp ends of the staples fold against the anvil 40 after
30 passing through the two layers of stomach wall tissue, thus maintaining the plication. If the mucosal reinforcements 72, 74 of Figs. 13A, 13B are used, the staples engage one or both mucosal reinforcing rings as during stapling.

The procedure may be repeated to form multiple plications if needed. Following formation of the plication(s), a medical implant may be coupled to the hole/incision
35 formed by the hollow needle 20. Coupling may be carried during the course of the same

procedure or during a later procedure scheduled to permit sufficient formation of adhesions between the serosal tissue layers 102 to support the implant.

The system or other components described herein may be packaged with instructions for use instructing a user to utilize the system according to methods disclosed
5 herein.

As is evident from above, the disclosed endoscopic systems function to draw a tissue into the stomach to form a depression on the exterior surface of the stomach, and staple (or suture, or fasten or adhere etc) the opposed stomach wall sections lining the depression together another to form a plication. The system may additionally place
10 material of a type that will promote strong tissue adhesion within the depression (on the exterior of the stomach) and retain the material between the serosal surfaces to enhance. Additionally or alternatively, mucosal reinforcements such as structures that interconnect the staples may be implanted. While these systems provide convenient embodiments for carrying out this function, there are many other widely varying instruments or systems
15 may alternatively be used within the scope of the present invention. Moreover, the disclosed embodiments may be combined with one another in varying ways to produce additional embodiments. Thus, the embodiments described herein should be treated as representative examples of systems useful for forming endoscopic tissue plications, and should not be used to limit the scope of the claimed invention.

20 Any and all patents, patent applications and printed publications referred to above, including those relied upon for purposes of priority, are incorporated herein by reference.

CLAIMS

We claim:

- 5 1. A method of stapling layers of tissue within a body cavity, comprising the steps of:
- positioning a stapler having a cartridge, an anvil and a stapling position between the cartridge and anvil, within the body cavity;
- passing an engaging instrument through the stapling position and engaging the
- 10 region of tissue using the engaging instrument;
- retracting the engaging instrument to move the engaged tissue into the stapling position; and
- driving staples from the cartridge through at least two layers of the engaged tissue.
- 15 2. The method of claim 1 wherein driving the staples from the cartridge includes driving a staple driver into the cartridge using fluid pressure.
3. The method of claim 1 wherein engaging the region of tissue includes applying suction to the region of tissue.
- 20 4. The method of claim 1 wherein engaging the region of tissue includes pinching the region of tissue.
5. The method of claim 1 wherein driving the staples forms a fold of stapled tissue.
- 25 6. The method of claim 1 wherein driving the staples includes driving the staples through a reinforcing element adjacent to the engaged tissue, causing the staples to engage the reinforcing element.
- 30 7. The method of claim 5 wherein the method includes positioning the reinforcing element adjacent to the anvil prior to driving the staples.
8. The method of claim 5 wherein the method includes positioning the reinforcing element adjacent to the cartridge prior to driving the staples.

9. The method of claim 1, further including advancing at least one of the anvil and cartridge to compress the engaged tissue prior to driving the staples.
10. The method of claim 1, further including forming a cut through the engaged tissue
5 using a cutting element other than a staple.
11. The method of claim 10 wherein forming the cut includes forming a cutout through the tissue.
- 10 12. The method of claim 11 wherein the staples encircle the cutout.
13. The method of claim 3, wherein the suction is applied to a first surface of the tissue, and wherein the method further includes expanding an engaging element adjacent a second surface of the tissue opposite from the first, the engaging element including a
15 tether extending through the tissue, and wherein moving the engaged tissue includes pulling the engaging element to move the engaged tissue into the stapling position.
14. The method of claim 13 wherein driving the staples includes driving the staples through the engaging element.
- 20 15. The method of claim 1, further including introducing a shaft into the body cavity, a distal portion of the shaft including a first branch having the cartridge and anvil thereon and a second branch having the engaging instrument thereon, and wherein engaging the region of tissue includes passing the second branch between the cartridge and anvil.
- 25 16. The method of claim 15 wherein moving the region of tissue includes withdrawing the second branch to draw the engaged tissue into the stapling position.
17. A stapling system, including:
30 a stapler head on a first elongate shaft, the stapler head having a cartridge containing staples and an anvil; and
an engaging instrument on a second elongate shaft, , the engaging instrument advanceable in a first direction from a first position on a first side of the stapler head, between the cartridge and anvil, to a second position on a second side of the stapler head
35 and into engagement with tissue on the second side, the engaging instrument retractable

in a second direction from the second position to retract engaged tissue to a stapling position between the cartridge and anvil.

18. The stapling system including:

5 a main shaft having a distal portion, wherein the first elongate shaft forms a first branch of the distal portion and the second elongate shaft forms a second branch of the distal portion.

19. The stapling system according to claim 17, wherein the engaging instrument
10 includes a vacuum head.

20. The stapling system according to claim 17, wherein the engaging instrument including a grasping element.

15 21. The stapling system according to claim 17, further including a reinforcing element positioned adjacent the cartridge and/or anvil such that staples driven from the cartridge engage the reinforcing element.

22. The stapling system according to claim 17, further including a cutting element
20 operatively associated with the stapler head to form a cut through tissue during stapling using staples in the cartridge.

23. The stapling system according to claim 21 wherein the cutting element is a punch
shaped to punch a hole through the tissue.

25

24. The stapling system according to claim 21 wherein the cutting element is positioned such that the cut is formed to be surrounded by staples.

25. The stapling system according to claim 19 wherein the vacuum head is
30 collapsible.

26. The stapling system according to claim 17, further including a piston coupled to a staple driver, a chamber housing the piston, and a fluid source fluidly coupled to the housing, the staple driver positioned such that directing fluid from the fluid source into
35 the chamber advances the staple driver to the staple cartridge.

27. The stapling system according to claim 26, further include a cutting element carried by the staple driver into engagement with tissue during advancement of the staple driver.

5

28. The stapling system according to claim 17, further including a piston coupled to the cartridge, a chamber housing the piston, and a fluid source fluidly coupled to the housing, the cartridge positioned such that directing fluid from the fluid source into the chamber advances the cartridge towards the anvil for tissue compression.

10

29. A method of reinforcing an array of staples delivered to tissue, the method comprising;

providing a staple reinforcement comprising a framework having at least one member and at least one opening;

15

positioning the staple reinforcement adjacent to a anvil or cartridge of a stapler;

positioning body tissue between the cartridge and anvil;

simultaneously driving a plurality of staples from the cartridge, causing legs of the staples to fold around the member.

20



30. The method of claim 29, wherein driving the staples causes legs of the staples to pass through the at least one opening.


31. The method of claim 30, wherein the reinforcement is provided to include a lattice having a plurality of openings, and wherein driving the staples causes a plurality of legs
25 to pass through a plurality of the openings.


32. The method of claim 31 wherein the reinforcement is a lattice having the plurality of openings.


30


33. The method of claim 31, further including the step of allowing tissue ingrowth to form in a plurality of the openings.



















ENGAGE VACUUM
PORT
SUCK TISSUE

FIG 7A




ENGAGE
DEPLOY NEEDLE

FIG 7B



DEPLOY BALLOON

FIG 7C



INFLATE BALLOON

FIG 7D

RETRACT NEEDLE AND
PULL ON BALLOON TO
LOCATE/TISSUE.
MANIPULATE

FIG 7E







Fig. 8






FIG. 12A




FIG. 12B




FIG. 12C




FIG. 11A




FIG. 11B




FIG. 13A






FIG. 13B

**FIG. 14A**

TOP VIEW OF ANVIL SIDE
STAPLE RING.






FIG. 14C




FIG. 15A




FIG. 15B




FIG. 16a




FIG. 16b





FIG. 17

FIG. 18A



1.




FIG. 18B

Pierce & Deploy, + INFLATE
TISSUE




FIG. 18C

PULL AND STAPLE




FIG. 18D

PULL STRING CONNECTION
ALSO MADE OF
DISSOLVABLE MATERIAL




FIG. 18E






FIG. 19






FIG. 21A




FIG. 21B




FIG. 21C




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B17/068 A61B17/072
 ADD. A61B17/00 A61B17/30 A61B17/115

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97/47231 A (BOSTON SCIENT CORP [US]) 18 December 1997 (1997-12-18) page 10, line 21 - page 14, line 11 figures 1-5	17,18, 20-22, 24,26-28
X	WO 2004/110285 A (ETHICON SPA [IT]; BILOTTI FEDERICO [IT]; D ARCANGELO MICHELE [IT]; LON) 23 December 2004 (2004-12-23) page 21, line 1 - page 22, line 26 page 9, line 14 - page 10, line 20 figures 18a-18l	17,18, 20,21, 26,28
X	WO 03/099137 A (NDO SURGICAL INC [US]; CERIER JEFFREY C [US]; CRUZ AMOS [US]; O'KEEFE) 4 December 2003 (2003-12-04) page 18, line 7 - page 19, line 10 figures 9B-9E	17,18,20
-/-		

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

12 February 2008

Date of mailing of the international search report

20/02/2008

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Compos, Fabien

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2007/019833

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2004/032760 A (TYCO HEALTHCARE [US]; ROY PHILIP C [US]) 22 April 2004 (2004-04-22) page 2, line 16 - page 3, line 16 figures 1,2 -----	26,28

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2007/019833

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 1-16, 29-33
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2007/019833

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
WO 9747231	A	18-12-1997	AT	320219 T		15-04-2006
			CA	2258128 A1		18-12-1997
			DE	69735485 T2		12-10-2006
			EP	0910289 A2		28-04-1999
			JP	3488245 B2		19-01-2004
			JP	2000512185 T		19-09-2000
			US	6302311 B1		16-10-2001
			US	6119913 A		19-09-2000
<hr/>						
WO 2004110285	A	23-12-2004	AU	2003245952 A1		04-01-2005
			BR	PI0318356 A		01-08-2006
			CA	2529450 A1		23-12-2004
			CN	1859874 A		08-11-2006
			EP	1633256 A1		15-03-2006
			JP	2006527600 T		07-12-2006
			MX	PA05013759 A		27-06-2006
<hr/>						
WO 03099137	A	04-12-2003	US	2004010245 A1		15-01-2004
<hr/>						
WO 2004032760	A	22-04-2004	AU	2003279151 A1		04-05-2004
			CA	2500785 A1		22-04-2004
			EP	1545331 A2		29-06-2005
<hr/>						